

## **DELAWARE COUNTY ENGINEERING DEPARTMENT DRIVEWAY INSTALLATION SPECIFICATIONS**

If this application to construct a driveway entrance and approach is granted the applicant agrees to the following applicable provisions:

- 1) All drainage pipes used in the construction of driveways and approaches shall be specified by the County Engineering Department as necessary for proper drainage.
- 2) All driveway and approaches shall be constructed so that they shall not interfere with drainage of the street or highway.
- 3) No more entrances or approaches shall be permitted connecting any County Highway with any single property than are necessary to adequately accommodate the traffic that may reasonably be expected.
- 4) No entrance or approach shall be located or constructed so as to interfere with or prevent the proper location of necessary highway signage.
- 5) The permittee shall assume responsibility for all maintenance of such approaches from the right of way line to a point thirty (30) inches from the edge of the traveled roadway. The approach pavement within thirty (30) inches of the edge of the traveled roadway, where the traveled roadway is hard surfaced, shall be hard surfaced. Where the approach pavement meets the edge of the existing roadway, the approach pavement shall be graded so as to match the existing edge of pavement elevation.
- 6) No such entrance or approach shall be relocated or its dimensions altered without written permission of the County Highway Engineer.
- 7) The permittee shall remove or relocate any such entrances when requested to do so by the County Commissioners in the interest of safety to highway traffic.
- 8) Commercial driveways may be required to provide an all-truck turn-around, truck route, and a traffic impact analysis.
- 9) The right of way adjacent to or between the approaches shall be graded so as to remove storm water. Such areas shall be finished in a manner that will prevent vehicular encroachment if necessary.
- 10) Drainage pipe when necessary shall be corrugated metal pipe of no less than sixteen (16) gauge and shall be of such length as required to provide no greater slope than 2.1 from the edge of the driveway pavement to the flow line of the side ditch.
- 11) An application under these regulations shall be made on this form and if necessary drawings shall be submitted with and become a part of the permit agreement. When the proposed driveway and approach can be clearly defined by filling in dimension on typical standard drawings the applicant may do so in lieu of submitting drawings.

**\*\*\*SEE ATTACHED DRAWINGS**